Crane & Hoist Monthly Inspection Checklist Page 1 of 2

| # | Inspection Item | Yes | No | N/A |
|----|---|-----|----|-----|
| 1 | Conduct pre-use inspection of equipment. Does it pass the pre-use inspection? (See Appendix A) | | | |
| 2 | Any deformed, cracked, or corroded members? | | | |
| 3 | Are there worn, cracked, or distorted parts such as pins, bearings, wheels, shafts, gears, rollers, locking and clamping devices, bumpers, and stops? | | | |
| 4 | Is there excessive wear or improper operation of the brake system parts, linings, pawls, chain sprockets or ratchets? | | | |
| 5 | Any cracked or worn sheaves and drums? | | | |
| 6 | Are there loose or missing bolts, nuts, pins or rivets? | | | |
| 7 | Is there any signs of pitting or deterioration of controllers, master switches, contacts, limit switches, and push button stations? | | | |
| 8 | Are load, wind, and other indicators properly operating? | | | |
| 9 | Are gasoline, diesel, electric, or other power plants performing properly? | | | |
| 10 | Are stops provided at the limit of travel of the trolley? | | | |
| 11 | Corroded, cracked, bent, worn, or improperly applied end connections? | | | |
| 12 | Load chain reeving for compliance with hoist manufacturer's recommendation? | | | |

Appendix B <u>Crane & Hoist Monthly Inspection Checklist</u> <u>Page 2 of 2</u>

| | <u>Hook</u> | | | | |
|---|---|--|--|--|--|
| 13 | Is there any gouges, nicks, weld spatter, corrosion, deformation, cracks? | | | | |
| 14 | Has the hook throat opening increased 5%, not to exceed ¼ inch (6 mm), more than the normal throat opening measured at the narrowest point? | | | | |
| 15 | Is there any bend or twist from the plane of the unbent hook? | | | | |
| | <u>Chain</u> | | | | |
| 16 | Is there excessive drive chain stretch? | | | | |
| 17 | Test the hoist under load in lifting and lowering directions and observe the operation of the chain and sprockets. Does the chain feed smoothly into and away from the sprockets? | | | | |
| 18 | Does the chain bind, jump, or is noisy? If so, clean chain. If trouble continues inspect the chain and mating parts for wear, distortion, or other damage. | | | | |
| 19 | Slacken the chain and move the adjacent links to one side to inspect for wear at the contact points. Is wear observed? Is stretching suspected? | | | | |
| Refer to owner's manual for any additional inspection items: Comments: | | | | | |
| Crane ID number or identifier: | | | | | |